

TDCNS - Troffer Dish Center Basket (Narrow Basket - Shallow Body)

Premium-Grade Recessed Shallow Body Direct/Indirect Center Baffle T-Bar Luminaire

Product Specifications - Application Features

Premium-grade, shallow body recessed, lay-in direct/indirect coffered T-Bar troffer with modern styling and high visual comfort. For use with indoor applications where low-glare, high-quality and ease of installation are required. This luminaire comes with a narrow single basket-shaped perforated metal shield.



Product Specifications

Optical System

Narrow basket shield is perforated for direct/indirect illumination and contains a translucent white opal acrylic overlay, which is secured in place with spring latches. Indirect reflectors are precision formed and contoured to provide soft, low-glare, indirect illumination, while maintaining high-efficiency and a wide uniform lighting distribution.

Mounting

This luminaire has been specifically designed for T-Bar applications. Holes provided for chain-mounting support to building structure. Integral earthquake clips.

Construction

Die-formed and riveted heavy-gauge steel housing assembly. Die-formed, perforated cold rolled steel shielding. Precision-formed steel reflector.

Finish

White polyester powder painted visible surfaces.

Electrical

Rotary lampholders ensure positive lamp retention. All electrical components are CSA approved or UL listed. See product selection for optional ballasts. Sufficient knockouts are provided for connections and through wiring.

Approvals

Approved to CSA and UL standards (UL, or equivalent, marked only when specified).

Notes

Product Features

- Available with 1, 2, 3 or 4 lamps
- Available in 1 x 4, 2 x 2 and 2 x 4 configurations
- Shallow housing well-suited for reduced plenum space
- Translucent, opal white acrylic diffuser overlay
- Single, narrow basket-shaped perforated metal shield
- Available in T5 and PLL/Biax configurations

Options & Adders

- Lamps available (please specify colour temperature and wattage)
- Multi-level switching
- Dimmable ballast
- Emergency ballast
- Radio interference filter (120V - 277V)
- 2 x 2 and 2 x 4 flange kits available (see page 243)
- 20 gauge heavy-duty construction
- Flexible metal whip - 6 foot x 3/18 gauge conductors
- Modular wiring system (consult factory)

Applications

- Classrooms
- Corridors
- Office Areas
- Retail Stores & Supermarkets



*Certain features and configurations may not be available. Consult the factory for more information.

