



# GREENBEAM LED



## DC150LUS DIECAST WALLPACKS PRODUCT INFORMATION

<b>Housing:</b>	Die Cast Aluminum
<b>Finish:</b>	Weather Resistant Dark Bronze Powder Coat*
<b>Lens:</b>	Clear Prismatic Borosilicate Glass
<b>Mounting Options:</b>	Directly over 4" outlet box or surface wired through 1/2" conduit entries.
<b>Mounting Height:</b>	Up to 30 feet
<b>LEDs:</b>	Mid-power Samsung LEDs or high-power Philips Lumileds.
<b>Operating Voltage:</b>	100-277 VAC 60/60Hz
<b>Power Factor:</b>	>0.98
<b>Max Ambient Temp:</b>	Pending Final Testing
<b>Rated Life:</b>	50,000 HRS
<b>DLC Qualified:</b>	No
<b>Environment:</b>	Outdoor; Wet Location
<b>Certifications/Approvals</b>	<b>ETL LISTED US AND CANADA, IP 66 RATED</b> <b>CONFORMS TO:</b> <b>UL-8750, UL-1598, CSA22.2</b>
<b>Warranty:</b>	3 year standard. 5 year available.

\*May be available in other finishes. Contact for details.



**14W-42W**  
CAN REPLACE UP TO:  
**250W HID**

## DC150LUS

The **DC150LUS** is a corrosion resistant Wallpack designed to provide the long life and high reliability required in industrial and commercial applications. These lights are ideal for providing safety and security along building perimeters.

## FEATURES & BENEFITS

- Uses up to **88% less energy** than HID equivalent
- **3-5x longer life** than fluorescent or HID systems
- Mercury and UV free with **RoHS certified LEDs**
- Designed and **Assembled in the USA**
- Instant On/Off

## DC150LUS ORDERING GUIDE\*

MODEL		WATTS	COLOR TEMPERATURE	OPTIONAL ACCESSORIES
<b>DC150LUS</b>	Medium Wallpack	<b>14W</b>	<b>30K</b> 3000K- Warm White	<b>OS</b> Occupancy Sensor
		<b>28W</b>	<b>40K</b> 4000K- Neutral White	<b>DIM</b> Dimmable Driver
		<b>42W</b>	<b>50K</b> 5000K- Cool White	<b>PC</b> Photocell
			<b>55K</b> 5500K- Daylight	

\* Standard configuration in bold. Specifications may be subject to change without notice.



**DESIGNED AND  
ASSEMBLED IN THE USA**

SEPARATE MULTIPLE ACCESSORIES WITH A PERIOD IN THE ORDER LISTED ABOVE

EXAMPLE:

**DC150LUS.28W.40K.OS** = Occupancy Sensor

**DC150LUS.28W.40K.OS.DIM** = Occupancy Sensor, Dimmer



## DC150LUS CONFIGURED SPECIFICATIONS\*

PRODUCT NUMBER**	INPUT WATTS	COLOR TEMPERATURE	INITIAL LUMENS	EFFICACY (lm/W)	CRI
DC150LUS .14W.30K	14W	3000K	1600lm	114	>80
DC150LUS .14W.40K	14W	4000K	1600lm	114	>80
DC150LUS .14W.50K	14W	5000K	1600lm	114	>80
DC150LUS .14W.55K	14W	5500K	1600lm	114	>60
DC150LUS .28W.30K	28W	3000K	3200lm	114	>80
<b>DC150LUS .28W.40K</b>	<b>28W</b>	<b>4000K</b>	<b>3200lm</b>	<b>114</b>	<b>&gt;80</b>
DC150LUS .28W.50K	28W	5000K	3200lm	114	>80
DC150LUS .28W.55K	28W	5500K	3200lm	114	>60
DC150LUS .42W.30K	42W	3000K	4800lm	114	>80
DC150LUS .42W.40K	42W	4000K	4800lm	114	>80
DC150LUS .42W.50K	42W	5000K	4800lm	114	>80
DC150LUS .42W.55K	42W	5500K	4800lm	114	>60

\* Specs reflect nominal values. \*\* Standard configuration in bold. Specifications may be subject to change without notice.

## DIMENSIONS

NOTE: DRAWINGS MAY NOT TO BE SCALE.



## ACCESSORIES AND EXTRAS

Pictures are representative, accessories and options may change based on spec or availability.

IMAGE NOT AVAILABLE

### Occupancy Sensor

ADD: .OS

Add motion-detected automatic on/off switching.



### Photocell

ADD: .PC

Add automatic on/off switching based on ambient light. Internal button-type is standard.



### Dimmable Driver

ADD: .DIM

Add dimming capabilities to your fixture with a 0-10V dimming driver.