



# GREENBEAM LED



## DCSHM200L90US DIECAST WALLPACKS FULL CUT-OFF PRODUCT INFORMATION

<b>Housing:</b>	Die Cast Aluminum
<b>Finish:</b>	Weather Resistant Dark Bronze Powder Coat*
<b>Lens:</b>	Heat and Impact Resistant Tempered Glass
<b>Mounting Options:</b>	Directly over 4" outlet box or surface wired through 1/2" conduit entries.
<b>Mounting Height:</b>	Up to 30 feet
<b>LEDs:</b>	Mid-power Samsung LEDs or high-power Philips Lumileds.
<b>Operating Voltage:</b>	100-277 VAC 60/60Hz
<b>Power Factor:</b>	>0.98
<b>Max Ambient Temp:</b>	Pending Final Testing
<b>Rated Life:</b>	50,000 HRS
<b>DLC Qualified:</b>	Pending
<b>Environment:</b>	Outdoor; Wet Location
<b>Certifications/ Approvals</b>	<b>ETL LISTED US AND CANADA, IP 66 RATED</b> <b>CONFORMS TO:</b> <b>UL-8750, UL-1598, CSA22.2</b>
<b>Warranty:</b>	3 year standard. 5 year available.

\*May be available in other finishes. Contact for details.

### E-Z MOUNT

EXTERNAL MOUNTING PLATE INCLUDED. NO NEED TO OPEN.



**14W-42W**  
CAN REPLACE UP TO:  
**250W HID**

### DCSHM200L90US

The **DCSHM200L90US** is a corrosion resistant Full Cut-Off Wallpack designed to provide the long life and high reliability required in industrial and commercial applications. These lights are ideal for providing safety and security along building perimeters.

### FEATURES & BENEFITS

- Uses up to **88% less energy** than HID equivalent
- **3-5x longer life** than fluorescent or HID systems
- Mercury and UV free with **RoHS certified LEDs**
- Designed and **Assembled in the USA**
- Instant On/Off
- **Zero sight-line** meets "Dark Sky" requirements

### DCSHM200L90US ORDERING GUIDE\*

MODEL	WATTS	COLOR TEMPERATURE	OPTIONAL ACCESSORIES
<b>DCSHM200L90US</b> Half Moon	14W	30K 3000K- Warm White	OS Occupancy Sensor
	<b>28W</b>	<b>40K</b> 4000K- Neutral White	DIM Dimmable Driver
	42W	50K 5000K- Cool White	
		55K 5500K- Daylight	

\* Standard configuration in bold. Specifications may be subject to change without notice.



**DESIGNED AND ASSEMBLED IN THE USA**

SEPARATE MULTIPLE ACCESSORIES WITH A PERIOD IN THE ORDER LISTED ABOVE

EXAMPLE:

**DCSHM200L90US .28W.40K.OS** = Occupancy Sensor

**DCSHM200L90US .28W.40K.OS.DIM** = Occupancy Sensor, Dimmer



## DCSHM200L90US CONFIGURED SPECIFICATIONS\*

PRODUCT NUMBER**	INPUT WATTS	COLOR TEMPERATURE	INITIAL LUMENS	EFFICACY (lm/W)	CRI
DCSHM200L90US.14W.30K	14W	3000K	1600lm	114	>80
DCSHM200L90US.14W.40K	14W	4000K	1600lm	114	>80
DCSHM200L90US.14W.50K	14W	5000K	1600lm	114	>80
DCSHM200L90US.14W.55K	14W	5500K	1600lm	114	>60
DCSHM200L90US.28W.30K	28W	3000K	3200lm	114	>80
<b>DCSHM200L90US.28W.40K</b>	<b>28W</b>	<b>4000K</b>	<b>3200lm</b>	<b>114</b>	<b>&gt;80</b>
DCSHM200L90US.28W.50K	28W	5000K	3200lm	114	>80
DCSHM200L90US.28W.55K	28W	5500K	3200lm	114	>60
DCSHM200L90US.42W.30K	42W	3000K	4800lm	114	>80
DCSHM200L90US.42W.40K	42W	4000K	4800lm	114	>80
DCSHM200L90US.42W.50K	42W	5000K	4800lm	114	>80
DCSHM200L90US.42W.55K	42W	5500K	4800lm	114	>60

\* Specs reflect nominal values. \*\* Standard configuration in bold. Specifications may be subject to change without notice.

## DIMENSIONS

NOTE: DRAWINGS MAY NOT TO BE SCALE.



## ACCESSORIES AND EXTRAS

Pictures are representative, accessories and options may change based on spec or availability.

IMAGE NOT  
AVAILABLE

### Occupancy Sensor

Add motion-detected automatic on/off switching.

ADD: .OS



### Dimmable Driver

Add dimming capabilities to your fixture with a 0-10V dimming driver.

ADD: .DIM

ADD: .OP1 or .OP2